

Schedule 40 PVC Pipe Dimensions

| TRADE SIZE | OD | ID | MIN. T. | WATER PRESSURE |
|------------|--------|--------|---------|-----------------------|
| (IN) | (IN) | (IN) | (IN) | RATING AT 23°C (73°F) |
| 1/2 | 0.840 | 0.609 | 0.109 | 600 |
| 3/4 | 1.050 | 0.810 | 0.113 | 480 |
| 1 | 1.315 | 1.033 | 0.133 | 450 |
| 1-1/4 | 1.660 | 1.363 | 0.140 | 370 |
| 1-1/2 | 1.900 | 1.593 | 0.145 | 330 |
| 2 | 2.375 | 2.049 | 0.154 | 280 |
| 2-1/2 | 2.875 | 2.445 | 0.203 | 300 |
| 3 | 3.500 | 3.042 | 0.216 | 260 |
| 4 | 4.500 | 3.998 | 0.237 | 220 |
| 6 | 6.625 | 6.031 | 0.280 | 180 |
| 8 | 8.625 | 7.942 | 0.322 | 160 |
| 10 | 10.750 | 9.976 | 0.365 | 140 |
| 12 | 12.750 | 11.889 | 0.406 | 130 |
| 14 | 14.000 | 13.073 | 0.437 | 130 |
| 16 | 16.000 | 14.940 | 0.500 | 130 |

Standard Color: White, Standard Length 10' & 20', Plain End and Belled End Purple color for reclaim. Contact us for more details.



Lead the safer electrical conduit systems

<https://www.ledestube.com/>